

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

APLLICATIONS

This high quality ATF can be used in automatic transmissions with torque convertors of passenger cars, as well as in wet clutches and power steering units.

FEATURES

Frictional properties: very smooth gear shifting, no vibration. Anti-wear protection: significantly extended transmission life. Extended oil life: excellent thermal and oxidation stability

PERFORMANCE LEVEL

DEXRON VI
MERCON LV
MB 236.1/236.5/236.7/236.8/236.9/236.41
VAG G-055-025/G-052-162
AISIN WARNER JWS 3309/3324 (WS)
ALLISON TES 228/C3/C4
BMW ETL7045/7045E/8072B/LA2634/
MINI COOPER T-IV
BMW 83222167720
CHRYSLER DODGE MOPAR AS68RC (TYPE IV)
CHRYSLER DODGE MOPAR ATF+/+2/+3/+4
FIAT TYPE IV
FORD MERCON /WSS-M2C138-CJ/166-H/922-A1/924-A
GM DEXRON IID/IIE/IIIG/IIIH/TASA

HONDA ACURA DW-1/ATF-Z1 (EXCEPT IN CVT)
HYUNDAI/KIA SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
HYUNDAI/KIA JWS3314/9683
ISUZI BESCO ATF II/III, NISSAN MATIC C/D/J/K/S
JAGUAR ATF 3403 M115/JLM 20238
JASO M315-2013 1A/1A-LV/2A
MAZDA ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317
MITSUBISHI SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA
OPEL, PORSCHE ATF 3403-M115/TYPE IV
SUBARU ATF/ATF 5AT/ATF HP
SUZUKI ATF 3309/3314/3317/2326/2384 K
TOYOTA D-II/D-III/T-III/T-IV/WS
VOITH 55.6335
VOLVO 1161540/97340
ZF 5HP 18FL/19FL/24A/30/4 HP 20, ZF TE-ML 11A/11B

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.847
Viscosity 40°C	mm²/s	30
Viscosity 100°C	mm²/s	6.0
Viscosity index		151
Brookfield viscosity at -40 °C	mPas	12000
Color		Red

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

