

ATF 8

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

- excellent contribution to fuel economy
- excellent lubrication
- very good resistance against oxidation
- very good thermal stability
- excellent and very stable friction characteristics
- excellent resistance against corrosion and foaming
- excellent protection against wear

FEATURES

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

PERFORMANCE LEVEL

ZF 8 HP	CHRYSLER 68157995AA	JAGUAR 02JDE26444	VW 060 162
BMW 83222152426	FIAT 9.55550-AV5	LAND ROVER LR 023288	

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.845
Viscosity 40°C	mm ² /s	28.10
Viscosity 100°C	mm ² /s	5.94
Viscosity index		164
Flash Point COC	°C	210
Pour Point	°C	-48
Brookfield viscosity at -40 °C	mPas	9500
Color		Green

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

