

# ATF 9

## SYNTHETIC MOTOR OIL.

A very high graded, extremely low-viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- excellent contribution to fuel economy
- excellent lubrication
- very good resistance against oxidation
- very good thermal stability
- excellent and very stable friction characteristics
- excellent resistance against corrosion and foaming
- excellent protection against wear
- a very high and stable viscosity index

### APPLICATIONS

This premium synthetic product is specially formulated for the lubrication of certain Mercedes-Benz automatic transmissions with 9 gears. This oil contributes significantly to realizing fuel saving and can be used in automatic transmissions where an oil with the specification MB 236.17 is prescribed

### PERFORMANCE LEVEL

MB 236.17

### CHARACTERISTICS

|                 | UNIT               | AVERAGE VALUE |
|-----------------|--------------------|---------------|
| Density at 15°C | kg/l               | 0.835         |
| Viscosity 40°C  | mm <sup>2</sup> /s | 17.10         |
| Viscosity 100°C | mm <sup>2</sup> /s | 4.23          |
| Viscosity index |                    | 161           |
| Flash Point COC | °C                 | 190           |
| Pour Point      | °C                 | -54           |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

