

RACING 5W40

SYNTHETIC MOTOR OIL.

A universal, ester fortified, synthetic motor oil developed according the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATIONS

This is a universal, ester fortified, synthetic motor oil. This Oil is specially developed for passenger car engines. Moreover this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging with or without DPF (Diesel particulate filter).

PERFORMANCE LEVEL

API SN/CF	VW 505 00/505 01	BMW LONGLIFE 04	FORD M2C917-A	RENAULT RN 0700/RN 0710
ACEA C3	MB 229.31/226.5	GM DEXOS 2	PORSCHE A40	FIAT 9.55535-S2

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.850
Viscosity 40°C	mm ² /s	92.18
Viscosity 100°C	mm ² /s	15.80
Viscosity index		183
Flash Point COC	°C	243
Pour Point	°C	-42
Total Base Number	mgKOH/g	7.4
Viscosity -30°C	mPas	4469

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

