

SUPER 0W/16

SYNTHETIC MOTOR OIL.

A fuel economy SAE 0W/16 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a good resistance against shearing
- a very fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

APPLICATIONS

This fuel economy, specially composed SAE 0W/16 motor oil, is recommended for use in petrol engines in passenger cars of Japanese OEMs, equipped with the latest techniques.

PERFORMANCE LEVEL

API SN

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.846
Viscosity 40°C	mm ² /s	37.90
Viscosity 100°C	mm ² /s	7.10
Viscosity index		154
Flash Point COC	°C	216
Pour Point	°C	-39
Total Base Number	mgKOH/g	7.2
Viscosity -35°C	mPas	5830
Sulphate Ash	%	0.88

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

