

SUPER 5W/30

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, providing outstanding wear and sludge protection, even under the most severe driving conditions. Due to its enhanced frictional properties, improved fuel economy is obtained.

APPLICATIONS

This motor oil has been specially designed to meet the latest requirements for most American and Asian passenger cars, SUV's and light vans. Originally intended for fuel-injected gasoline engines, including turbo-charging and multi-valves, it can also be used in light duty diesel engines without particulate filters.

PERFORMANCE LEVEL

API SN/CF	BMW LONGLIFE-01	OPEL GM-LL-B-25	VW 502 00/505 00
ACEA A3/B4	MB 226.5/229.3	RENAULT RN 0700	

FEATURE

- Total engine protection: outstanding engine cleanliness and durability.
- Cold start: excellent fluidity at low temperature.
- Fuel economy: lower fuel consumption and CO2 emissions.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.856
Viscosity 40°C	mm ² /s	64.3
Viscosity 100°C	mm ² /s	10.9
Viscosity index		162
Flash Point COC	°C	228
Pour Point	°C	-45
Total Base Number	mgKOH/g	8.1
Viscosity -30°C	mPas	6300
Sulphate Ash	%	0.88

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

