

# SUPER 5W40

## SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils and high quality additives of the latest generation, specially designed to meet the strict requirements of manufacturers. This provides an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.

### APPLICATIONS

This oil is used in gasoline engines of cars, which demand the highest performance and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

### PERFORMANCE LEVEL

API SN/CF	BMW LONGLIFE-01	OPEL GM-LL-B-025	PORSCHE A40	RENAULT RN 0700/0710
ACEA A3/B4	MB 226.5/229.3	FIAT 9.55535-M2	PSA B71 2296	VW 502 00/505 00

### FEATURE

- Total engine protection : performance in keeping the engine clean.
- Cold start : excellent fluidity at low temperature.
- Drain interval extension : longer oil drain interval.

### CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.853
Viscosity 40°C	mm <sup>2</sup> /s	90.2
Viscosity 100°C	mm <sup>2</sup> /s	15
Viscosity index		175
Flash Point COC	°C	223
Pour Point	°C	-42
Total Base Number	mgKOH/g	10.5
Viscosity -30°C	mPas	5740
Sulphate Ash	%	1.33

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

