SUPER FORD **01/30**



This fully synthetic, fuel economy "Mid SAPS" motor oil was developed in collaboration with Ford for the EURO 6 Duratorq TDCi engines in the latest models (2014 -...) with exhaust after treatment and turbocharger. The high-tech VI improver provides high stability to ensure long oil change intervals. The product is especially suitable for the use of biofuels, the composition was formulated so as to prevent chain wear.

APPLICATIONS

These fully synthetic motor oil suitable for the latest EURO 6 TDCI Duratorq engines from Ford, where the manufacturer a product dictates that meets the specification FORD WSS M2C950-A but can also be used for all other petrol, LPG and diesel engines with or without turbo. where a type 0W30 viscosity is prescribed by ACEA C2.

PERFORMANCE LEVEL

ACEA C2

JAGUAR LAND ROVER STJRL 03 5007

FORD WSS M2C950 A

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.845
Viscosity 40°C	mm²/s	49.3
Viscosity 100°C	mm²/s	10
Viscosity index		189
Flash Point COC	°C	206
Pour Point	°C	-45
Total Base Number	mgKOH/g	7.7
Sulphate ash	%	0.80
Viscosity -35°	mPas	5800

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

