

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is extremely fuel-efficient and meets the requirements of the new Ford EcoBoost petrol engines. It ensures a reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission. It has excellent cold starting behavior giving a very good operating reliability.

APPLICATIONS

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA A1/B1 or API SN.

PERFORMANCE LEVEL

ACEA C5, A1/B1	JAGUAR LAND ROVER STJLR.03.5004
API SN	FORD WSS-M2C948-B

FEATURES

- Total engine protection : performance in keeping the engine clean.
- Fuel economy : superior fuel economy and CO2 reduction.
- Cold start : excellent fluidity at low temperature.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.851
Viscosity 40°C	mm²/s	42.3
Viscosity 100°C	mm²/s	7.9
Viscosity index		162
Flash Point COC	°C	220
Pour Point	°C	-39
Total Base Number	mgKOH/g	7.6
Viscosity -30°C	mPas	5500

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

