

# SUPER FORD 5W/30

## SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, especially developed for the requirements of Ford WSS-M2C913-C/D specifications. It is characterized by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications.

### APPLICATIONS

It is mandatory for all Ford models (gasoline and diesel, also those with particulate filter) from 2009 onwards. It's also required for the vehicles equipped with the 2,2 Duratorq TDCI engines and is fully backwards compatible with all current Ford diesel engines, with the exception of the models which are equipped with pump injectors (Galaxy I en II) and Ford KA (diesel and gasoline from 2009).

### PERFORMANCE LEVEL

ACEA A1-B1 / A5-B5      FORD WSS-M2C913-C/D      JAGUAR / LAND ROVER STJR.03.5003  
API SL/CF                  RENAULT RN 0700

### FEATURES

- Fuel economy : superior fuel economy and CO2 reduction.
- Total engine protection : performance in keeping the engine clean .
- Cold start : excellent fluidity at low temperature .

### CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.853
Viscosity 40°C	mm <sup>2</sup> /s	53.3
Viscosity 100°C	mm <sup>2</sup> /s	9.66
Viscosity index		168
Flash Point PM	°C	206
Pour Point	°C	-45
Total Base Number	mgKOH/g	10.1
Viscosity -30C	mPas	4200
Sulphate ash	%	1.09

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

