

# SUPER G2 0W/20

## SYNTHETIC MOTOR OIL.

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion

### APPLICATIONS

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2.

### PERFORMANCE LEVEL

API SN/RC/SN+	GM DEXOS 1 GEN 2	FORD M2C945-A/ 46-A/ 47-A
ILSAC GF 5	CHRYSLER MS6395	

### CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.843
Viscosity 40°C	mm <sup>2</sup> /s	44.00
Viscosity 100°C	mm <sup>2</sup> /s	8.60
Viscosity index		178
Flash Point COC	°C	222
Pour Point	°C	-39
Total Base Number	mgKOH/g	8.5
Sulphate ash	%	0.89
Viscosity -35°	mPas	4940

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

