

# SUPER G2 5W/30

## SYNTHETIC MOTOR OIL.

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

## APPLICATIONS

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2.

## PERFORMANCE LEVEL

API SN/SN+/SN+RC	GM DEXOS 1 GEN 2	FORD M2C9946-A
ILSAC GF 5	CHRYSLER MS6395	

## CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.851
Viscosity 40°C	mm <sup>2</sup> /s	61.8
Viscosity 100°C	mm <sup>2</sup> /s	11.30
Viscosity index		179
Flash Point COC	°C	224
Pour Point	°C	-30
Total Base Number	mgKOH/g	8.5
Sulphate ash	%	0.89
Viscosity -30°	mPas	4140

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

