

SUPER GM 5W/30

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, for the lubrication of all gasoline and diesel engines with turbocharging. Due to the excellent fluidity at low temperature and low resistance at start this product is fuel saving. Exceptional viscosity index and high thermal stability.

APPLICATIONS

This oil can be used in 4-stroke gasoline engines, four-valve, turbo. 4-stroke diesel engines with or without turbo, without diesel particulate filter (DPF).

PERFORMANCE LEVEL

API SL/CF VW 501 01/505 00
ACEA A3/B4 MB 229.1

FEATURE

- Total engine protection: performance in keeping the engine clean.
- Cold start: excellent fluidity at low temperature.
- Drain interval extension: longer oil drain interval.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.860
Viscosity 40°C	mm ² /s	58.60
Viscosity 100°C	mm ² /s	10.10
Viscosity index		161
Flash Point COC	°C	230
Pour Point	°C	-33
Total Base Number	mgKOH/g	8.1
Viscosity -30°C	mPas	6290

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /
Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

