

SUPREME 0W/20 LL III

SYNTHETIC MOTOR OIL.

A fuel economy, fully synthetic motor oil, developed according the most recent technology, based on specially selected fully synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- lower fuel consumption
- reduced formation of combustion residues (mid SAPS)
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming
- dark green color

APPLICATIONS

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. This oil can only be used in engines which prescribe an oil with the specification VW 508.00/509.00

PERFORMANCE LEVEL

VW 508.00/509.00
PORSCHE C20

CHARACTERISTICS

| | UNIT | AVERAGE VALUE |
|-------------------|--------------------|---------------|
| Density at 15°C | kg/l | 0.832 |
| Viscosity 40°C | mm ² /s | 39.30 |
| Viscosity 100°C | mm ² /s | 7.93 |
| Viscosity index | | 179 |
| Flash Point COC | °C | 220 |
| Pour Point | °C | -57 |
| Total Base Number | mgKOH/g | 8.3 |
| Sulphate ash | % | 0.78 |
| Viscosity -35°C | mPas | 3330 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /
Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

