

SUPREME 0W/30 C2

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, specially developed for the PSA EURO VI Blue HDi DW10F engines with exhaust after treatment and turbocharger. This specification demands high stability to ensure long oil drain intervals. It also addresses the use of biofuels. There is a fuel economy benefit over a 5W40 reference oil of 4,2%.

APPLICATIONS

This product was primarily developed for mandatory use in the PSA EURO VI Blue HDi DW10F engines and particularly ones equipped with e-HDI using Stop & Start technologies. This product is also usable for other OEM's passenger cars requiring this viscosity grade and ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's cars with extended service intervals.

PERFORMANCE LEVEL

ACEA C2 FIAT 9.55535-GS1

PSA B71 2312 FIAT 9.55535-DS1

FEATURES

- Total engine protection : performance in keeping the engine clean.
- Fuel economy : superior fuel economy and CO2 reduction.
- Cold start : excellent fluidity at low temperature.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.849
Viscosity - 35°C	mPas	5920
Viscosity 40°C	mm ² /s	55.10
Viscosity 100°C	mm ² /s	9.80
Viscosity index		160
Flash Point COC	°C	230
Pour Point	°C	-51
Total Base Number	mgKOH/g	6.2
Sulphate ash	%	0.54

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

