

SUPREME 0W/30 LL III

SYNTHETIC MOTOR OIL.

A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATIONS

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

PERFORMANCE LEVEL

ACEA C2*/C3

VW 504.00/507.00

* does not exceed FE of ACEA C2

PORSCHE C30

FEATURES

- After treatment protection: full aftertreatment system protection.
- Total engine protection: outstanding engine cleanliness and durability.
- Fuel economy: superior fuel economy and CO2 reduction.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.842
Viscosity 40°C	mm ² /s	64.00
Viscosity 100°C	mm ² /s	12.00
Viscosity index		178
Flash Point COC	°C	195
Pour Point	°C	-51
Total Base Number	mgKOH/g	8.3
Sulphate ash	%	0.78
Viscosity -35°C	mPas	5750

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

