

SUPREME 5W/30 C2

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils. This high-performance engine oil with low viscosity is specifically developed to provide the highest fuel economy and lowest CO2 emissions.

APPLICATIONS

Specifically recommended for Peugeot and Citroën gasoline and diesel engines equipped with diesel particulate filters. Most Japanese OEM's, including Toyota, Honda, Subaru and Nissan.

PERFORMANCE LEVEL

ACEA C2 FIAT 9.55535-S1 RENAULT RN 0700

API SN/CF PSA B71 2290

FEATURES

- After treatment protection: full aftertreatment system protection.
- Total engine protection: outstanding engine cleanliness and durability.
- Fuel economy: superior fuel economy and CO2 reduction.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.853
Viscosity - 30°C	mPas	5550
Viscosity 40°C	mm ² /s	61.70
Viscosity 100°C	mm ² /s	10.50
Viscosity index		160
Flash Point COC	°C	236
Pour Point	°C	-45
Total Base Number	mgKOH/g	7.7
Sulphate ash	%	0.76

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

