

SUPREME 5W/30 C3

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated to meet Euro 4 and Euro 5 norms and the demanding MB 229.51 specifications, and to ensure exceptional performance in terms of oxidation resistance, soot and sludge formation. It is a MidSAPS oil of the latest generation with low sulfated ash, sulfur and phosphorus content. It provides complete protection of after-treatment devices and Diesel Particulate Filters.

APPLICATIONS

Euro 4 and 5 gasoline and diesel engines of Mercedes Benz, Smart and Chrysler vehicles that are equipped with a DPF. Fully backwards compatible for engines of previous generations (Euro 1, 2, 3).

PERFORMANCE LEVEL

ACEA C3

API SN

BMW LONGLIFE-04

MB 229.51 / 229.31

VW 502 00 / 505 00 / 505 01

FEATURES

- Total engine protection: Outstanding engine cleanliness and durability.
- After Treatment protection: Complete protection of the DPF filter.
- Fuel economy: Lower fuel consumption and CO2 emissions.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.851
Viscosity - 30°C	mPas	5540
Viscosity 40°C	mm ² /s	68.90
Viscosity 100°C	mm ² /s	12.10
Viscosity index		175
Flash Point COC	°C	228
Pour Point	°C	-39
Total Base Number	mgKOH/g	7.1

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

