

SUPREME 5W/30 LL III

SYNTHETIC MOTOR OIL.

A fuel economy, fully synthetic motor oil, developed according the most recent technology, based on specially selected fully synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- LOW SAPS content
- suitable for modern catalyts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATIONS

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

PERFORMANCE LEVEL

ACEA C3	MB 229.51	PORSCHE C30
API SN	BMW LL 04	

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.851
Viscosity 40°C	mm ² /s	69.20
Viscosity 100°C	mm ² /s	12.00
Viscosity index		171
Flash Point COC	°C	230
Pour Point	°C	-42
Total Base Number	mgKOH/g	6.7
Sulphate ash	%	0.67
Viscosity -30°C	mPas	5950

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

VROMAN NV /

Oudenaardestraat 49, 8570 Vichte - Belgium / T+32 (0)56 72 62 29

