

SUPREME 5W40 C3

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is formulated with excellent additives to meet the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine. It is a Mid SAPS oil (sulfated ash, phosphorus and sulfur content), which corresponds to Euro 4 and Euro 5 norms. It provides reliable protection of after-treatment devices and Diesel Particulate Filters. The oil is very universal in use and can be used for petrol and diesel engines.

APPLICATIONS

Specifically recommended for the lubrication of all TDI engines with pump injectors and for Common Rail turbo diesel engines. SUPREME 5W40 C3 is also perfect for the lubrication of the latest generation Petrol cars.

PERFORMANCE LEVEL

ACEA C3	API SN/CF	BMW LONGLIFE-04	MB 226.5/ 229.51 / 229.31	VW 502 00 / 505 00 / 505 01
GM dexos 2	RN 0700/0710	FORD WSS-M2C917-A	PORSCHE A40	FIAT: 9.55535-S2

FEATURES

- After treatment protection: full aftertreatment system protection.
- Total engine protection: outstanding engine cleanliness and durability.
- Fuel economy: superior fuel economy and CO2 reduction.

CHARACTERISTICS

	UNIT	AVERAGE VALUE
Density at 15°C	kg/l	0.850
Viscosity - 30°C	mPas	5500
Viscosity 40°C	mm ² /s	82.80
Viscosity 100°C	mm ² /s	14.00
Viscosity index		175
Flash Point COC	°C	232
Pour Point	°C	-42
Total Base Number	mgKOH/g	7.4
Sulphate ash	%	77

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

